

Appln. No. 10/635,354
Amdt. dated December 1, 2004
Reply to Office Action of October 26, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1 1. (currently amended) A mounting bracket with an ejection
2 means for detachable retaining of a cylindrical tank member
3 with respect to a wall surface comprising:
 - 4 A. a backing plate member securable to a wall surface;
 - 5 B. an upper clamping member extending outwardly away from
6 said backing plate member and defining a tank storage
7 zone means for selectively receiving and holding of a
8 cylindrical tank member therewithin, said upper
9 clamping member including:
 - 10 (1) an upper clamp base means secured to said backing
11 plate member to facilitate securement of said
12 upper clamping member fixedly with respect to said
13 backing plate member;
 - 14 (2) a first upper clamp arm means secured to and
15 extending outwardly from said upper clamp base
16 means to engage the cylindrical tank member for
17 facilitating retaining thereof selectively in said
18 tank storage zone means with the cylindrical tank
19 member in abutment with respect to said first
20 upper clamp arm means;
 - 21 (3) a second upper clamp arm means secured to and
22 extending outwardly from said upper clamp base
23 means at a position spatially disposed oppositely
24 from said first upper clamp arm means, said first
25 upper clamp arm means and said second upper clamp
26 arm means defining said tank storage zone means
27 therebetween which is particularly adapted to
28 receive a cylindrically shaped tank member
29 therewithin, said second upper clamp arm means
30 adapted to abut the cylindrical tank member
31 oppositely from said first upper clamp arm means
32 responsive to the cylindrical tank member being
33 positioned in said tank storage zone means to
34 facilitate selective retaining of the
35 cylindrically shaped tank member with respect to
36 said backing plate member;
 - 37 C. a lower clamping member extending outwardly away from
38 said backing plate member at a position below said
39 upper clamping member and further defining the tank
40 storage zone means for selectively receiving and

41 holding of a cylindrical tank member therewithin, said
42 lower clamping member including:

- 43 (1) an lower clamp base means secured to said backing
44 plate member to facilitate securement of said
45 lower clamping member fixedly with respect to said
46 backing plate member;
47 (2) a first lower clamp arm means secured to and
48 extending outwardly from said lower clamp base
49 means to engage the cylindrical tank member for
50 facilitating retaining thereof selectively in said
51 tank storage zone means with the cylindrical tank
52 member in abutment with respect to said first
53 lower clamp arm means;
54 (3) a second lower clamp arm means secured to and
55 extending outwardly from said lower clamp base
56 means at a position spatially disposed oppositely
57 from said first lower clamp arm means, said first
58 lower clamp arm means and said second lower clamp
59 arm means further defining said tank storage zone
60 means therebetween which is particularly adapted
61 to receive a cylindrically shaped tank member
62 therewithin, said second lower clamp arm means
63 adapted to abut the cylindrical tank member
64 oppositely from said first lower clamp arm means
65 responsive to the cylindrical tank member being
66 positioned in said tank storage zone means to
67 facilitate selective retaining of the
68 cylindrically shaped tank member with respect to
69 said backing plate member;

70 D. an ejection means secured to said backing plate member
71 and adapted in steady state to exert a force
72 continuously against the cylindrical shape of a
73 cylindrical tank member positioned within said tank
74 storage zone means for urging ejecting movement thereof
75 outwardly therefrom, said ejection means being capable
76 of being forced to move to a compressed position to
77 allow the cylindrical tank member to be retained in
78 said tank storage zone means; ~~[[and]]~~

79 E. a restraining means attached with respect to said
80 backing plate member and adapted to engage the
81 cylindrical tank member for selective retaining thereof
82 within said tank storage zone means and for retaining
83 of said ejection means in the compressed position in
84 abutment with respect to the cylindrical tank member
85 responsive to retaining of the cylindrical tank member
86 in said tank storage zone means; and

87 F. a lower shelf member secured to said backing plate
88 member and extending outwardly therefrom to provide
89 lower support for a cylindrical tank member positioned
90 in said tank storage zone means, said lower shelf
91 member extending outwardly from said backing plate
92 member at an angle with respect thereto of greater than

93 ninety degrees to facilitate passive ejection of a
94 cylindrical tank member from said tank storage zone
95 means unless retained therewithin by said restraining
96 means.

1 2. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 1 wherein said
4 restraining means includes a restraining strap means secured
5 to said backing plate member and adapted to extend around a
6 cylindrical tank member positioned within said tank storage
7 zone means for retaining same therewithin and for forcibly
8 holding said ejection means in the compressed position.

1 3. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 2 wherein said
4 restraining strap means is flexible and wherein said
5 restraining means further includes:
6 A. a first clasping means attached with respect to said
7 backing plate member and extending outwardly therefrom;
8 B. a second clasping means attached with respect to said
9 restraining strap means and detachably engageable with
10 respect to said first clasping means to detachably
11 secure said restraining strap means in position
12 extending around a cylindrical tank member positioned
13 in said tank storage zone means with said ejection
14 means held in the compressed position.

1 4. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 3 wherein said
4 first clasping means is fixedly secured rigidly with respect
5 to said backing plate member to facilitate selective
6 detachment and detachable securement of said second clasping
7 means with respect to said first clasping means by a user
8 while simultaneously allowing holding of the cylindrical
9 tank member within said tank storage zone means by the user.

1 5. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 1 further
4 comprising an ejection zone means defined between said
5 backing plate member and said tank storage zone means to
6 facilitate positioning of said ejection means therewithin
7 secured to said backing plate member.

1 6. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 5 wherein said
4 ejection means is adapted in the steady state to extend
5 outwardly from said ejection zone means into said tank

6 storage zone means to exert a force against a cylindrical
7 tank member positioned therewithin.

1 7. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 6 wherein said
4 ejection means is entirely contained within said ejection
5 zone means responsive to being moved to the compressed
6 position thereof.

1 8. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 1 wherein said
4 ejection means includes a flat spring means which is
5 flexibly resilient.

1 9. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 8 wherein said
4 ejection means further includes a bumper means secured to
5 said flat spring means for facilitating the exerting of
6 force against a cylindrical tank member positioned within
7 said tank storage zone means while minimizing damaging
8 thereof.

1 10. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 1 wherein said
4 upper clamping member further includes:
5 A. a first upper extension arm means fixedly secured to
6 said upper clamp base means and extending outward
7 therefrom approximately perpendicularly with respect to
8 said backing plate member, said first upper extension
9 arm means being fixedly secured to said first upper
10 clamp arm means which extends outwardly therefrom to
11 define said tank storage zone means thereadjacent; and
12 B. a second upper extension arm means fixedly secured to
13 said upper clamp base means and extending outward
14 therefrom approximately perpendicularly with respect to
15 said backing plate member, said second upper extension
16 arm means being approximately parallel to and spatially
17 disposed from said first upper extension arm means,
18 said second upper extension arm means being fixedly
19 secured to said second upper clamp arm means which
20 extends outwardly therefrom to facilitate defining of
21 said tank storage zone means thereadjacent, said first
22 upper extension arm means and said second upper
23 extension arm means being large enough to position said
24 tank storage zone means, spatially located between said
25 first upper clamp arm means and said second upper clamp
26 arm means, at a sufficient distance from said backing
27 plate member to facilitate mounting of said ejection

28 means on said backing plate member between said backing
29 plate member and said tank storage zone means.

1 11. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 10 wherein
4 said lower clamping member further includes:
5 A. a first lower extension arm means fixedly secured to
6 said lower clamp base means and extending outward
7 therefrom approximately perpendicularly with respect to
8 said backing plate member, said first lower extension
9 arm means being fixedly secured to said first lower
10 clamp arm means which extends outwardly therefrom to
11 define said tank storage zone means thereadjacent; and
12 B. a second lower extension arm means fixedly secured to
13 said lower clamp base means and extending outward
14 therefrom approximately perpendicularly with respect to
15 said backing plate member, said second lower extension
16 arm means being approximately parallel to and spatially
17 disposed from said first lower extension arm means,
18 said second lower extension arm means being fixedly
19 secured to said second lower clamp arm means which
20 extends outwardly therefrom to facilitate defining of
21 said tank storage zone means thereadjacent, said first
22 lower extension arm means and said second lower
23 extension arm means being large enough to position said
24 tank storage zone means, spatially located between said
25 first lower clamp arm means and said second lower clamp
26 arm means, at a sufficient distance from said backing
27 plate member to facilitate mounting of said ejection
28 means on said backing plate member between said backing
29 plate member and said tank storage zone means.

1 12. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 11 wherein the
4 distance between said first upper extension arm means and
5 said second upper extension arm means is less than the size
6 of the cylindrical tank member to prevent positioning
7 thereof therebetween and wherein the distance between said
8 first lower extension arm means and said second lower
9 extension arm means is also less than the size of the
10 cylindrical tank member to prevent positioning thereof
11 therebetween.

1 13. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 1 wherein said
4 first upper clamp arm means, said second upper clamp arm
5 means, said first lower clamp arm means and said second
6 lower clamp arm means each include a protective coating
7 applied thereover by dipping which minimizes damaging of a

8 cylindrical tank member retained within said tank storage
9 zone means.

1 14. (canceled)

1 15. (canceled)

1 16. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 3 wherein said
4 restraining strap means includes:

5 A. an upper strap section attached with respect to said
6 backing plate member and extending outwardly therefrom,
7 said upper strap section extending around a cylindrical
8 tank member positioned within said tank storage zone
9 means and said being attached with respect to said
10 first clasp means for detachable securement
11 therearound; and

12 B. a lower strap section attached with respect to said
13 backing plate member at a location beneath said upper
14 strap section and extending outwardly therefrom, said
15 lower strap section extending around a cylindrical tank
16 member positioned within said tank storage zone means
17 and said being attached with respect to said first
18 clasp means for detachable securement therearound.

1 17. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 16 wherein
4 said upper strap section is attached to said backing plate
5 member at a position immediately below said upper clamping
6 member and wherein said lower strap section is attached to
7 said backing plate member at a position immediately below
8 said lower clamping member.

1 18. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 1 wherein said
4 ejection means is secured to said backing plate member at a
5 position below said upper clamping member and above said
6 lower clamping member to facilitate operative ejection of a
7 cylindrical tank member responsive to disengagement of said
8 restraining means.

1 19. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 10 wherein
4 said first upper clamp arm means, said first upper extension
5 arm means, said upper clamp base means, said second upper
6 extension arm means and said second upper clamp arm means
7 are formed integrally.

1 20. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface as defined in Claim 11 wherein
4 said first lower clamp arm means, said first lower extension
5 arm means, said lower clamp base means, said second lower
6 extension arm means and said second lower clamp arm means
7 are formed integrally.

1 21. (canceled)

1 22. (original) A mounting bracket with an ejection means for
2 detachable retaining of a cylindrical tank member with
3 respect to a wall surface comprising:

4 A. a backing plate member securable to a wall surface and
5 defining an ejection zone means immediately
6 thereadjacent;

7 B. an upper clamping member extending outwardly away from
8 said backing plate member and defining a tank storage
9 zone means adjacent said ejection zone means for
10 selectively receiving and holding of a cylindrical tank
11 member therewithin, said ejection zone means being
12 positioned between said tank storage zone means and
13 said backing plate member, said upper clamping member
14 including:

15 (1) an upper clamp base means secured to said backing
16 plate member to facilitate securement of said
17 upper clamping member fixedly with respect to said
18 backing plate member;

19 (2) a first upper clamp arm means secured to and
20 extending outwardly from said upper clamp base
21 means to engage the cylindrical tank member for
22 facilitating retaining thereof selectively in said
23 tank storage zone means in abutment with respect
24 to said first upper clamp arm means, said first
25 upper clamp arm means including a first upper
26 clamp arm protective coating applied thereover by
27 dipping which minimizes damaging of a cylindrical
28 tank member retained within said tank storage zone
29 means thereadjacent;

30 (3) a second upper clamp arm means secured to and
31 extending outwardly from said upper clamp base
32 means at a position spatially disposed oppositely
33 from said first upper clamp arm means, said first
34 upper clamp arm means and said second upper clamp
35 arm means defining said tank storage zone means
36 therebetween, said second upper clamp arm means
37 adapted to abut the cylindrical tank member
38 oppositely from said first upper clamp arm means
39 responsive to the cylindrical tank member being
40 positioned in said tank storage zone means to
41 facilitate selective retaining thereof with

42 respect to said backing plate member, said second
43 upper clamp arm means including a second upper
44 clamp arm protective coating applied thereover by
45 dipping which minimizes damaging of a cylindrical
46 tank member retained within said tank storage zone
47 means thereadjacent;
48 (4) a first upper extension arm means fixedly secured
49 to said upper clamp base means and extending
50 outward therefrom approximately perpendicularly
51 with respect to said backing plate member, said
52 first upper extension arm means being fixedly
53 secured to said first upper clamp arm means which
54 extends outwardly therefrom to define said tank
55 storage zone means thereadjacent;
56 (5) a second upper extension arm means fixedly secured
57 to said upper clamp base means and extending
58 outward therefrom approximately perpendicularly
59 with respect to said backing plate member, said
60 second upper extension arm means being
61 approximately parallel to and spatially disposed
62 from said first upper extension arm means, said
63 second upper extension arm means being fixedly
64 secured to said second upper clamp arm means which
65 extends outwardly therefrom to facilitate defining
66 of said tank storage zone means thereadjacent,
67 said first upper extension arm means and said
68 second upper extension arm means being large
69 enough to position said tank storage zone means,
70 spatially located between said first upper clamp
71 arm means and said second upper clamp arm means,
72 at a sufficient distance from said backing plate
73 member to facilitate mounting of said ejection
74 means on said backing plate member between said
75 backing plate member and said tank storage zone
76 means, said second upper extension arm means being
77 spatially disposed from said first upper extension
78 arm means at a distance less than the size of the
79 cylindrical tank member to prevent positioning
80 thereof therebetween;
81 C. a lower clamping member extending outwardly away from
82 said backing plate member at a position below said
83 upper clamping member and further defining the tank
84 storage zone means adjacent said ejection zone means
85 for selectively receiving and holding of a cylindrical
86 tank member therewithin, said ejection zone means being
87 positioned between said tank storage zone means and
88 said backing plate member, said lower clamping member
89 including:
90 (1) a lower clamp base means secured to said backing
91 plate member to facilitate securement of said
92 lower clamping member fixedly with respect to said
93 backing plate member;

94 (2) a first lower clamp arm means secured to and
95 extending outwardly from said lower clamp base
96 means to engage the cylindrical tank member for
97 facilitating retaining thereof selectively in said
98 tank storage zone means in abutment with respect
99 to said first lower clamp arm means, said first
100 lower clamp arm means including a first lower
101 clamp arm protective coating applied thereover by
102 dipping which minimizes damaging of a cylindrical
103 tank member retained within said tank storage zone
104 means thereadjacent;
105 (3) a second lower clamp arm means secured to and
106 extending outwardly from said lower clamp base
107 means at a position spatially disposed oppositely
108 from said first lower clamp arm means, said first
109 lower clamp arm means and said second lower clamp
110 arm means further defining said tank storage zone
111 means therebetween, said second lower clamp arm
112 means adapted to abut the cylindrical tank member
113 oppositely from said first lower clamp arm means
114 responsive to the cylindrical tank member being
115 positioned in said tank storage zone means to
116 facilitate selective retaining thereof with
117 respect to said backing plate member, said second
118 lower clamp arm means including a second lower
119 clamp arm protective coating applied thereover by
120 dipping which minimizes damaging of a cylindrical
121 tank member retained within said tank storage zone
122 means thereadjacent;
123 (4) a first lower extension arm means fixedly secured
124 to said lower clamp base means and extending
125 outward therefrom approximately perpendicularly
126 with respect to said backing plate member, said
127 first lower extension arm means being fixedly
128 secured to said first lower clamp arm means which
129 extends outwardly therefrom to define said tank
130 storage zone means thereadjacent;
131 (5) a second lower extension arm means fixedly secured
132 to said lower clamp base means and extending
133 outward therefrom approximately perpendicularly
134 with respect to said backing plate member, said
135 second lower extension arm means being
136 approximately parallel to and spatially disposed
137 from said first lower extension arm means, said
138 second lower extension arm means being fixedly
139 secured to said second lower clamp arm means which
140 extends outwardly therefrom to facilitate defining
141 of said tank storage zone means thereadjacent,
142 said first lower extension arm means and said
143 second lower extension arm means being large
144 enough to position said tank storage zone means,
145 spatially located between said first lower clamp

146 arm means and said second lower clamp arm means,
147 at a sufficient distance from said backing plate
148 member to facilitate mounting of said ejection
149 means on said backing plate member between said
150 backing plate member and said tank storage zone
151 means, said second lower extension arm means being
152 spatially disposed from said first lower extension
153 arm means at a distance less than the size of the
154 cylindrical tank member to prevent positioning
155 thereof therebetween;

156 D. an ejection means secured to said backing plate member
157 within said ejection zone means and adapted in steady
158 state to exert a force continuously against a
159 cylindrical tank member positioned within said tank
160 storage zone means for urging ejecting movement thereof
161 outwardly therefrom, said ejection means being capable
162 of being forced to move to a compressed position
163 completely positioned within said ejection zone means
164 to allow the cylindrical tank member to be retained in
165 said tank storage zone means, said ejection means being
166 secured to said backing plate member at a position
167 below said upper clamping member and above said lower
168 clamping member to facilitate operative ejection of a
169 cylindrical tank member unless said restraining means
170 is engaged, said ejection means including:

171 (1) a flat spring means which is flexibly resilient
172 and attached to said backing plate member;

173 (2) a bumper means secured to said flat spring means
174 for facilitating the exerting of force against a
175 cylindrical tank member positioned within said
176 tank storage zone means while minimizing damaging
177 thereof;

178 E. a restraining means comprising a restraining strap
179 means which is flexible and is attached with respect to
180 said backing plate member and adapted to extend around
181 the cylindrical tank member for selective retaining
182 thereof within said tank storage zone means and for
183 retaining of said ejection means in the compressed
184 position in abutment with respect to the cylindrical
185 tank member responsive to retaining of the cylindrical
186 tank member in said tank storage zone means, said
187 restraining means further including:

188 (1) a first clasping means attached with respect to
189 said backing plate member and extending outwardly
190 therefrom;

191 (2) a second clasping means attached with respect to
192 said restraining strap means and detachably
193 engageable with respect to said first clasping
194 means to detachably secure said restraining strap
195 means in position extending around a cylindrical
196 tank member positioned in said tank storage zone
197 means with said ejection means held in the

198 compressed position, said first clasping means
 199 being fixedly secured rigidly with respect to said
 200 backing plate member to facilitate selective
 201 detachment and detachable securement of said
 202 second clasping means with respect to said first
 203 clasping means by a user while simultaneously
 204 allowing holding of the cylindrical tank member
 205 within said tank storage zone means by the user;
 206 (3) an upper strap section attached with respect to
 207 said backing plate member and extending outwardly
 208 therefrom, said upper strap section extending
 209 around a cylindrical tank member positioned within
 210 said tank storage zone means and being attached
 211 with respect to said first clasping means for
 212 detachable securement therearound, said upper
 213 strap section being attached to said backing plate
 214 member at a position immediately below said upper
 215 clamping member;
 216 (4) an lower strap section attached with respect to
 217 said backing plate member at a location beneath
 218 said upper strap section and extending outwardly
 219 therefrom, said lower strap section extending
 220 around a cylindrical tank member positioned within
 221 said tank storage zone means and being attached
 222 with respect to said first clasping means for
 223 detachable securement therearound, said lower
 224 strap section being attached to said backing plate
 225 member at a position immediately below said lower
 226 clamping member; and
 227 F. a lower shelf member secured to said backing plate
 228 member and extending outwardly therefrom to provide
 229 lower support for a cylindrical tank member positioned
 230 in said tank storage zone means, said lower shelf
 231 member extending outwardly from said backing plate
 232 member at an angle with respect thereto of greater than
 233 ninety degrees to facilitate passive ejection of a
 234 cylindrical tank member from said tank storage zone
 235 means unless retained therewithin by said restraining
 236 means.

1 23. (previously presented) A mounting bracket with an ejection
 2 means for detachable retaining of a cylindrical tank member
 3 with respect to a wall surface comprising:
 4 A. a backing plate member securable to a wall surface;
 5 B. an upper clamping member extending outwardly away from
 6 said backing plate member and defining a tank storage
 7 zone means for selectively receiving and holding of a
 8 cylindrical tank member therewithin, said upper
 9 clamping member including:
 10 (1) an upper clamp base means secured to said backing
 11 plate member to facilitate securement of said
 12 upper clamping member fixedly with respect to said

13 backing plate member;
14 (2) a first upper clamp arm means secured to and
15 extending outwardly from said upper clamp base
16 means to engage the cylindrical tank member for
17 facilitating retaining thereof selectively in said
18 tank storage zone means in abutment with respect
19 to said first upper clamp arm means;
20 (3) a second upper clamp arm means secured to and
21 extending outwardly from said upper clamp base
22 means at a position spatially disposed oppositely
23 from said first upper clamp arm means, said first
24 upper clamp arm means and said second upper clamp
25 arm means defining said tank storage zone means
26 therebetween, said second upper clamp arm means
27 adapted to abut the cylindrical tank member
28 oppositely from said first upper clamp arm means
29 responsive to the cylindrical tank member being
30 positioned in said tank storage zone means to
31 facilitate selective retaining thereof with
32 respect to said backing plate member;
33 C. a lower clamping member extending outwardly away from
34 said backing plate member at a position below said
35 upper clamping member and further defining the tank
36 storage zone means for selectively receiving and
37 holding of a cylindrical tank member therewithin, said
38 lower clamping member including:
39 (1) an lower clamp base means secured to said backing
40 plate member to facilitate securement of said
41 lower clamping member fixedly with respect to said
42 backing plate member;
43 (2) a first lower clamp arm means secured to and
44 extending outwardly from said lower clamp base
45 means to engage the cylindrical tank member for
46 facilitating retaining thereof selectively in said
47 tank storage zone means in abutment with respect
48 to said first lower clamp arm means;
49 (3) a second lower clamp arm means secured to and
50 extending outwardly from said lower clamp base
51 means at a position spatially disposed oppositely
52 from said first lower clamp arm means, said first
53 lower clamp arm means and said second lower clamp
54 arm means further defining said tank storage zone
55 means therebetween, said second lower clamp arm
56 means adapted to abut the cylindrical tank member
57 oppositely from said first lower clamp arm means
58 responsive to the cylindrical tank member being
59 positioned in said tank storage zone means to
60 facilitate selective retaining thereof with
61 respect to said backing plate member;
62 D. an ejection means secured to said backing plate member
63 and adapted in steady state to exert a force
64 continuously on a cylindrical tank member positioned

65 within said tank storage zone means for urging ejecting
66 movement thereof outwardly therefrom, said ejection
67 means including a lower shelf member secured to said
68 backing plate member and extending outwardly therefrom
69 to provide lower support for a cylindrical tank member
70 positioned in said tank storage zone means, said lower
71 shelf member oriented extending outwardly from said
72 backing plate member at an angle of greater than ninety
73 degrees with respect thereto to facilitate passive
74 ejection of a cylindrical tank member from said tank
75 storage zone means unless restrained therewithin; and
76 E. a restraining means attached with respect to said
77 backing plate member and adapted to engage the
78 cylindrical tank member for selective retaining thereof
79 within said tank storage zone means.

1 24. (previously presented) A mounting bracket with an ejection
2 means for detachable retaining of a cylindrical tank member
3 with respect to a wall surface as defined in Claim 23
4 wherein said ejection means further includes a means to
5 exert a force laterally and continuously against a
6 cylindrical tank member positioned within said tank storage
7 zone means for urging ejecting movement thereof outwardly
8 therefrom which is urged to move to a compressed position
9 responsive to retaining of the cylindrical tank member in
10 said tank storage zone means.

1 25. (previously presented) A mounting bracket with an ejection
2 means for detachable retaining of a cylindrical tank member
3 with respect to a wall surface as defined in Claim 24
4 wherein said restraining means is adapted to retain said
5 ejection means in the compressed position in abutment with
6 respect to the cylindrical tank member responsive to
7 retaining of the cylindrical tank member in said tank
8 storage zone means.

1 26. (previously presented) A mounting bracket with an ejection
2 means for detachable retaining of a cylindrical tank member
3 with respect to a wall surface as defined in Claim 24
4 wherein said means to exert a force laterally and
5 continuously against a cylindrical tank member includes a
6 flat spring means which is flexibly resilient.